
P88 Series



Fully Encapsulated High Power Solution for up to 6 Lamp LCD Modules



- High Efficiency
- PCB Mountable
- Up to 6 CCFL Lamps
- Enable/Disable Control Pin
- .70 Inches (17,78 mm) High
- Up to 20 Watts of Output Power
- Operating Range of -30 to +70°C
- Fully Encapsulated for Resistance to Shock, Vibration and Humidity
- Designed, Manufactured and Supported in the USA
- One Year Warranty



Endicott Research Group, Inc.

2601 Wayne St., Endicott, NY 13760

607-754-9187 Fax 607-754-9255

<http://www.ergpower.com>



The drawing shows the mechanical specifications for a 10-pin package. The top view includes dimensions for the overall size (2.03 [51,6] x 1.800 [45,72]), pin pitch (1.000 [25,4]), and individual pin dimensions. The side view shows a height of 2.10 [53,4] and a maximum width of 0.700 [17,8]. A detail view shows the pin profile with a width of 0.120 [3,05] Min (Typ) and a thickness of 0.025 [0,64] Square (Typ).

Pin Designations	
Pin	Function
1	Vin
2	GND

Mass: 92 grams

Pin Designations	
Pin	Function
1	Vin
2	GND
3	Enable
4	AC Out
5	AC Out
6	AC Out
7	AC Out
8	AC Out
9	AC Out
10	AC Common



2601 Wayne St., Endicott, NY 13760
607-754-9187 Fax 607-754-9255
<http://www.ergpower.com>

P881 - 05/02